



Multi-Click

Generated on 22.06.2018

Detailed description

The Multi-Click vertical glazing system consists of 'X-structure' polycarbonate glazing panels which click together and are fitted within a thermally broken aluminium frame.

It requires no intermediate glazing bars, so provides an uninterrupted facade which results in higher light transmission and less shadows within a building.

Features and benefits:

- High impact strength.
- Excellent thermal insulation.
- Quick and easy to install.

Applications:

- Sports halls.
- Warehouses/ factories.
- Plant rooms.
- Partitions.
- Rooflights/ northlights.
- Cladding.

Product guidance - As Standard

Material:

- 40 mm Multi-Click Polycarbonate.
- Extruded aluminium bars to BS 1474.

Infill colour:

Clear.

Finish:

Polyester powder coating to BS 6496.

Primary cladding fixings:

Stainless steel self-tapping screws as recommended by Twinfix.

Panel width:

500 mm.

U-value (BS EN 673):

Twinfix Limited

TWINFIX

Twinfix Limited
201 Cavendish Place
Birchwood Park
Birchwood
Warrington
Cheshire
WA3 6WU

Tel: +44 (0)1925 811311

www.twinfix.co.uk
enquiries@twinfix.co.uk



0.99 W/m².

Fire performance:

Class B-s1,d0 to EN13501-1.

Maximum unsupported span:

2000 mm down the slope (assumed loadings; wind - 0.9 kN/m²).

Minimum pitch:

Vertical.

General:

- UV protection: To one side of sheet.
- Light transmission: Clear 52%, Pearlescent 44%
- Solar Heat Gain Coefficient : Clear 0.42, Pearlescent 0.28.

Product specification

Manufacturer

- Name: Twinfix Limited
- Web: www.twinfix.co.uk
- Email: enquiries@twinfix.co.uk
- Tel: +44 (0)1925 811311
- Fax: +44 (0)1925 852955
- Address: 201 Cavendish Place, Birchwood Park, Birchwood, Warrington, Cheshire WA3 6WU

Product reference Multi-Click

Colour

Accessories [None]
[Cill flashing]
[Head flashing]