



Twinfix Alu-Link-Panel System.



Twinfix Limited
201 Cavendish Place
Birchwood Park
Birchwood
Warrington
Cheshire
WA3 6WU

Tel: +44 (0)1925 811311

www.twinfix.co.uk
enquiries@twinfix.co.uk

Detailed description

Twinfix 2mm or 3mm Solid Aluminium Roof.

This roof system is light weight, weather resistant, and easy to install. Can be powder coated to any RAL colour.

Product guidance - As Standard

Material:

- 2mm pressed aluminium
- Extruded aluminium to BS 1474.

Finish:

Polyester powder coating to BS 6496.

Panel width:

250-350mm

Fire performance:

Aluminium is non-combustible
The panel is not fire rated

Primary cladding fixings:

Stainless steel self-tapping screws as recommended by Twinfix.

Maximum unsupported span:

1500 mm down the slope, 250-350 mm panel width (assumed loadings; wind - 0.9 kN/m²; snow - 0.5 kN/m²).

Maximum unsupported overhang:

150 mm.

Minimum Pitch:

3°.

General:

- Polyester powder coating on both sides of sheet.



Product specification

Manufacturer

- Name: Twinfix Limited
- Web: www.twinfix.co.uk
- Email: enquiries@twinfix.co.uk
- Tel: +44 (0)1925 811311
- Fax: +44 (0)1925 852955
- Address: 201 Cavendish Place, Birchwood Park, Birchwood, Warrington, Cheshire WA3 6WU

Product reference Twinfix Alu-Link-Panel System.

Type SA3

Colour [_____]

Accessories [None]