

# TWINFIX®

## Data Sheet Multi-Click

Vertical glazing system consisting of 40mm thick multiwall polycarbonate glazed into a thermally broken aluminium perimeter framework.

### Sizes Available

500mm panel width.  
Up to 7m panel length.

### Glazing

40mm thick multiwall polycarbonate which has a high impact strength and an excellent thermal insulation value of 0.99 W/m<sup>2</sup>K. The outer surface is UV protected for long life.

### Perimeter Framework

Polyester powder coated aluminium channel with integral thermal break all coated to a standard Twinfix RAL colour in a standard finish — (see colour availability chart).



### Colour Availability

Please note, the colours below are only for illustration and may not accurately represent the actual colour. Additional colours are available but may increase cost and lead times.



RAL9011  
Black



RAL9910  
White



RAL5010  
Blue



RAL3020  
Red



RAL1021  
Yellow



RAL6002  
Light  
Green



RAL6005  
Dark  
Green



RAL7037  
Light  
Grey



RAL7016  
Dark Grey



RAL9002  
Grey  
White



RAL7012  
Medium  
Grey

## Durability

Our polycarbonate combines high light transmission, good load bearing properties, and excellent weather resistance. The sheet is lightweight and impact resistant. It features a co-extruded UV-protective layer on one side of the sheet, which provides resistance against degradation caused by UV radiation in sunlight and almost no UV radiation passes through the sheet.

Our framework is polyester powder coated aluminium which is rust resistant, won't require future repainting and requires minimal maintenance.

## Guarantee

10-year warranty on materials and on all canopy installations fitted by one of our own teams.



# TWINFIX®

**Twifix Limited**  
201 Cavendish Place,  
Birchwood Park,  
Birchwood, Warrington,  
WA3 6WU

Tel: 01925 811311  
[enquiries@twifix.co.uk](mailto:enquiries@twifix.co.uk)  
[www.twifix.co.uk](http://www.twifix.co.uk)  
Registered in England. Company Number: 2457221

