



## Twinfix Cantilever Mono Pitch Canopy With Alu-Link Roof



Generated on 2.2.24

### Detailed description

The canopy structure comprises of a light weight, rust resistant aluminium frame that can be powder coated to any standard RAL colour with a pressed aluminium roof

### Approvals:

UKCE marked to EN 1090-1 - Execution of Steel & Aluminium Structures:

### Product guidance - As Standard

#### Material:

- Extruded aluminium roof and canopy structure to BS 1474.

#### Finish:

Polyester powder coating to BS 6496.

#### Panel width:

250-350 mm.

#### Fire performance:

Aluminium is non combustible  
The roof panels are not fire rated

#### Primary fixings:

Stainless steel self-tapping screws and stainless steel bolts/ nuts as recommended by Twinfix.

#### Maximum unsupported span:

1500 mm down the slope, 250-350 mm panel width (assumed loadings; wind - 0.9 kN/m<sup>2</sup>; snow - 0.5 kN/m<sup>2</sup>).

#### Maximum unsupported overhang:

150 mm.

#### Minimum Pitch:

3°.

#### Twinfix Limited

201 Cavendish Place  
Birchwood Park  
Birchwood  
Warrington  
Cheshire  
WA3 6WU

Tel: +44 (0)1925 811311

[www.twinfix.co.uk](http://www.twinfix.co.uk)  
[enquiries@twinfix.co.uk](mailto:enquiries@twinfix.co.uk)



General:

- Polyester powder coating to both sides of roof panel

**Product specification**

Manufacturer

- Name: Twinfix Limited
- Web: [www.twinfix.co.uk](http://www.twinfix.co.uk)
- Email: [enquiries@twinfix.co.uk](mailto:enquiries@twinfix.co.uk)
- Tel: +44 (0)1925 811311
- Fax: +44 (0)1925 852955
- Address: 201 Cavendish Place, Birchwood Park, Birchwood, Warrington, Cheshire WA3 6WU

**Product reference** Twinfix Cantilever Mono Pitch Canopy  
Glazed With Alu-Link Roof

**Type** Twinfix Mono Pitch aluminium canopy

**Colour**

- Frame [\_\_\_\_\_]

**Accessories** [None]  
[Aluminium side trims]  
[Head flashing]  
[Post protectors]  
[Ridge flashing]  
[Roller shutters]  
[Signage]  
[Vertical glazing]